

Verila CAG 2 VG15 ELT

Calcium Anhydrous Grease • For Extremely Low Temperatures, down to -50°C

Verila CAG 2 VG15 ELT is lubricating grease based on special calcium soap and mineral base oil of very low viscosity. The grease contains antioxidants, rust and corrosion inhibitors and AW additives. The product is water resistant, with improved corrosion protection and excellent low temperature performances.

- Excellent performance at Low Temperatures, suitable to be used in cold climates, down to -50 degrees Celsius.
- Very Good Mechanical stability makes it resistant against softening.
- Very Good Resistance against water.
- Very Good Lubricity, protect equipment against wear.
- Excellent Pump-ability makes it suitable for centralized lubrication systems.



Lubrication of high-speed rolling and plain bearings; Lubrication of small electro-motors and equipment working in cold climates, down to -50 degrees Celsius



Technical Data

Grease Classifications		
ISO 6743-9		L-XEBHA 2
DIN 51502		K2G-50
Test Parameter	Test Method	Value
Appearance	Visual	Smooth and Homogenous
Color	Visual	Light Yellow
Thickener		Calcium 12-Hydroxystearate
NLGI Grade	ASTM D217	2
Base Oil Viscosity at 40°C, mm ² /s	ISO 3104	15
Operating Temperature Range		-50 to 100 Celsius
Cone Penetration, Worked, 0.1 mm	ISO 2137	265 -295
Dropping Point	ISO 6299	> 145 Celsius
Water Resistance Test at 90°C	DIN 51 807-1	0-90 Typical

While the information and figures given here are typical of current production and compliant with VERILA specification, minor variations may occur